

Engine Reconditioning Range



Grinding / Cutting Fluids:

Syntol Aquagrind 750:

Synthetic soluble grinding fluid for use on all applications including, centre-less grinding, surface grinding & cylindrical grinding.

- Excellent corrosion protection.
- Very good bio-stability & low foam properties.
- Can machine most metals including mild, hardened, & stainless steels, aluminium.

Pack size available: 5 litres, 20 litres, 205 litres

Syntol Aquagrind 890:

Premium quality fully synthetic soluble grinding fluid designed for more arduous grinding applications such as grinding tool or other hardened steels.

- Excellent corrosion protection.
- Low foam characteristics.
- Additional lubricity for enhanced surface finish & hardened & tool steels.
- Excellent bio-stability.

Pack size available: 20 litres, 205 litres

Syntol Procut S38:

Multi-purpose general all rounder soluble cutting fluid, capable of dealing with all metal types & machining operations.

- Multi-metal, multi-operational extreme pressure fortified mineral based coolant
- Bio-stability additives incorporated to provide excellent resistance to bacteria & fungi.
- Excellent corrosion protection & foam control.

Pack size available: 5 litres, 20 litres, 60 litres, 205 litres

Mineral Oil Lubricants:

Syntol Hone 5000:

Premium performance honing oil for all honing applications.

- Applicable for all honing operations from hand held machines to large automated honing machines.
- Excellent lubricity characteristics allowing honing of arduous applications & giving a superior surface finish.
- Low aromatic content thereby does not attack seals, rubber hoses or machine paintwork.

Pack size available: 5 litres, 205 litres

Syntol Hydratek 32, 46, 68 Hydraulic Fluid:

Hydraulic Oils formulated from hydro-cracked virgin base stocks.

Available in ISO 32, 46 & 68 viscosity grades.

- Meets or exceeds: DIN51524, Part II: Cincinnati Machine P-68, P-69, P-70: Us Steel 126,127: AFNOR NFE 48-603 (HM): Vickers M-2950-S, I-286-S3: Denison HF-2, HF-0.
- Superior anti-wear & anti-oxidation properties ensuring longer oil drain life.
- Excellent hydrolytic stability enabling superior filtration performance.
- Excellent anti-foam & air release properties giving enhanced oxidation stability.

Pack size available: 20 litres, 205 litres

Syntol Slidelube 68 & 220 Slideway Oil:

Premium quality slide-way lubricants

- Applicable for all horizontal & vertical slides requiring & ISO 68 or ISO 220 viscosity oil.
- Excellent tackiness for adherence to slides.
- Anti-corrosion, friction modifying & extreme pressure additives incorporated for enhanced performance.

Pack size available: 20 litres, 205 litres

www.syntol.com



Spark Erosion Fluid:

Syntol Solvo SE110

Light viscosity spark erosion fluid with an elevated flash point (PMCC 110C).

- Elevated Flash point (PMCC 110C) for enhanced Health & Safety protection.
- Non- aromatic containing fluid protects hoses & parts from solvent degradation
- Clear colourless fluid & low odour.

Pack size available: 200 litres

Rust Preventatives:

Syntol Cortek RP85:

Light greasy film rust preventative which possess excellent de-watering & corrosion protection characteristics.

- Provides 3 - 6 months protection of moulds when stored inside.
- Excellent dewatering properties eliminating spot rusting.
- Light carrier solvent for a quicker dry-time.

Pack size available: aerosol, 5 litres, 20 litres, 205 litres

Syntol Cortek DF87:

Premium oil based de-watering fluid which imparts excellent rust preventative properties on metal parts, & machinery.

- Oil based product enabling easy removal.
- Excellent dewatering properties
- Excellent rust protection, giving 3 -6 months protection when stored inside.

Pack size available: aerosol, 5 litres, 20 litres, 205 litres

Cleaners:

Syntol Solvoclean SD:

Non-aromatic solvent designed to degrease parts in wash bath situation.

- Non aromatic containing solvent for operator acceptance.
- Non dangerous good classified solvent.
- Excellent grease cutting & oil dispersing properties.
- Leaves light film on work-pieces to act as temporary rust preventative.

Pack size available: 20 litres, 205 litres

Syntol Solvoclean T95:

Water-soluble turpentine based degreaser.

- Parts may be cleaned off with water after degreasing operation
- Very effective degreaser, dirt removing properties.

Pack size available: 20 litres, 205 litres

Syntol Super Ripper:

Multi-use biodegradable high quality water-based general purpose cleaner formulated to be used as a spray & wipe/wash type cleaner.

- Excellent removal of dirt, oil, grease & soils from all hard surfaces.

Pack size available: 4 litres, 20 litres, 205 litres

www.syntol.com

Email: info@syntol.com Freephone: 0800 syntol Phone: (09) 634 6004 Fax: (09) 634 6005