

Black Tapp



Product Description:

Black Tapp is a premium quality, extreme pressure fortified, multi-purpose tapping oil & may also be applicable for all forming & metal punching operations with all types of metals both ferrous & non-ferrous.

Product Applications:

Applicable primarily for tapping with all types of metals including mild, hardened and stainless steels, aluminium and copper and it's alloys. The excellent emulsification properties of Black Tapp enables easier removal of the oil from the work pieces after they have been formed.

Features & Benefits:

- Extreme pressure additives incorporated into the product
- High viscosity product
- Excellent emulsification properties
- Anti-corrosion additives incorporated
- Provides excellent lubricity enabling tapping procedures to be performed repeatedly even of deep or difficult metals being used in the tapping operation.
- Product sticks to the tap and metal surface enabling oil to be dragged into the tap as the process proceeds giving better lubrication.
- Allows for easy removal of oil from work pieces after the forming operation.
- Provides excellent anti-corrosion of work pieces.

Physical Properties:

Test	Units	Result
Density	gm/ml	1.12typ.
Appearance		Clear/bright dark brown fluid
Emulsion @ 10% in water		Stable
pH 10% in water		9.2

Health & Safety:

Syntol Black Tapp is a petroleum based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact is kept to a minimum. At no time should Syntol Black Tapp be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Black Tapp MSDS. For further H&S advice contact Syntol NZ Ltd. Phone (09) 634 6004.

Disclaimer:

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.