

Cortek RP95



Product Description

A heavy duty rust preventative giving excellent protection to steel & galvanized steel components, wire ropes & other metallic materials which may be exposed to the outside environment for 3 - 6 months.

Product Applications

Applicable for protection of metal parts & wire ropes which are exposed to severe conditions of water, either fresh or salt, for extended periods of time. May be used in cold conditions down to -15°C without cracking or peeling as seen in other types of heavy duty rust preventatives. Can be applied by brushing, swabbing, drip feed or soaking/dipping.

Features & Benefits

- Excellent adhesion to metal surfaces
- Very good lubricity characteristics
- Biodegradable
- Provides excellent rust protection & resists removal by rubbing / scrapping of metal surfaces.
- Provides very good lubrication of metal parts which are in contact with each other e.g. wire ropes in contact with mandrels etc.
- Suitable for use in environmentally sensitive applications such as at sea or other water ways, in forestry etc.

Physical Properties

Test	Units	Result
Appearance		Dark brown mobile liquid
Appearance of residue		Dark brown non tacky grease
Density	g/ml	0.85
Flash Point	°C	5
Solids	w/w%	51 typical

Health & Safety

Syntol Cortek RP95 is a moderate toxicity liquid. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Syntol Cortek RP95 is kept to a minimum. At no time should Cortek RP95 be disposed of into sewers. Disposal into storm water drains or other waterways should always be avoided. If spillage occurs contact your local council authority or refer to the Syntol Cortek RP95 MSDS. For further advice refer to Syntol NZ Ltd. Phone 09 6346004.

Disclaimer

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.