

# Lubricut 85



## Product Description

Lubricut 85 is a premium quality, extreme pressure fortified, multi-purpose neat cutting oil. Applicable for all machining operations with all types of metals both ferrous & non-ferrous.

## Product Applications

Applicable for all machining operations including cutting, reaming, gear hobbing, turning, milling, tapping, & broaching. Suitable for all metal types including steels, mild, hardened, & stainless, aluminium, copper and copper alloys.

## Features & Benefits

- Extreme pressure additives incorporated into the product
  - Provides excellent lubrication giving superior surface finish
- Anti-oxidant additives
  - Provides oxidation stability for longer oil life

## Physical Properties

Test	Units	Result
Density	gm/ml	0.92typ.
Appearance		Clear/bright dark brown fluid
Viscosity @ 40C	Cst	35 typ.

## Health & Safety

Syntol Lubricut 85 is a petroleum based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Lubricut 85 is kept to a minimum. At no time should Syntol Lubricut 85 be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Lubricut 85 MSDS. For further H&S advice contact Syntol NZ Ltd. Phone 09 6346004.

## Disclaimer

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.