

Lubricut 88



Product Description

A premium quality, multi-purpose neat cutting oil, applicable for all machining operations with all types of metals both ferrous & non-ferrous.

Product Applications

Applicable for all machining operations including cutting, reaming, turning, milling, tapping, & broaching. Suitable for all metal types including steels, mild, hardened, & stainless, aluminium, & copper & its alloys.

Features & Benefits

- Extreme pressure additives incorporated into the product
 - Provides excellent lubrication giving superior surface finish
- Anti-oxidant additives incorporated
 - Provides oxidation stability thereby avoiding gum deposit buildup on machinery

Physical Properties

Test	Units	Result
Density	gm/ml	0.9typ.
Appearance		Clear/bright amber fluid
Viscosity @ 40C	Cst	30 - 32

Health & Safety

Syntol Lubricut 88 is a petroleum based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Lubricut 88 is kept to a minimum. At no time should Syntol Lubricut 88 be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Lubricut 88 MSDS. For further H&S advice contact Syntol NZ Ltd. Phone 09 6346004.

Disclaimer

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.