

Lubriform 40



Product Description:

A premium quality, extreme pressure fortified, multi-purpose neat forming oil, applicable for all forming & metal punching operations with all types of metals both ferrous & non-ferrous.

Product Applications:

Applicable for all forming operations including deep drawing, punching, & general metal deformation work. The excellent emulsification properties allows for the ability to dilute or to use neat & wash off after the forming operation.

Features & Benefits:

- Extreme pressure additives incorporated into the product
- Excellent emulsification properties
- Anti-corrosion additives incorporated
- Provides excellent lubricity thereby minimizing dye pickup & metal tearing or scratching.
- Allows for prior dilution or to be used neat & washed off after the forming operation.
- Provides excellent anti-corrosion of work pieces.

Physical Properties:

Test	Units	Result
Density	gm/ml	1.10typ.
Appearance		Clear/bright dark brown fluid
Emulsion @ 10% in water		Stable
pH 10% in water		9.2

Health & Safety:

Syntol Lubriform 40 is a petroleum based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Lubriform 40 is kept to a minimum. At no time should Syntol Lubriform 40 be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Lubriform 40 MSDS. For further H&S advice contact Syntol NZ Ltd. Phone (09) 634 6004.

Disclaimer:

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.