

Lubriform 780



Product Description

A premium quality, extreme pressure fortified, multi-purpose neat forming oil, applicable for all forming & metal punching operations with all types of metals both ferrous & non-ferrous.

Product Applications

Applicable for all forming operations including deep drawing, punching, & general metal deformation work. The excellent emulsification properties allows for easier removal of the oil from the work pieces after they have been formed.

Features & Benefits

- Extreme pressure additives incorporated into the product
 - Provides excellent lubricity thereby minimizing dye pickup, metal tearing or scratching
- Excellent emulsification properties
 - Allows for easy removal of oil from work pieces after the forming operation
- Anti-corrosion additives incorporated
 - Provides excellent anti-corrosion of work pieces

Physical Properties

Test	Units	Result
Density	gm/ml	1.12typ.
Appearance		Clear/bright dark brown fluid
Emulsion @ 10% in water		Stable
pH 10% in water		8.0

Health & Safety

Syntol Lubriform 780 is a petroleum based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Lubriform 780 is kept to a minimum. At no time should Syntol Lubriform 780 be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Lubriform 780 MSDS. For further H&S advice contact Syntol NZ Ltd. Phone 09 6346004.

Disclaimer

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.