

Lubriform 788



Product Description:

Lubriform 788 is a premium quality, water based emulsion with extreme pressure additives for multi-purpose forming oil applications. Is applicable for all metal types including ferrous & non-ferrous.

Product Applications:

Applicable for all forming operations including deep drawing, punching, & general metal deformation work. The excellent emulsification properties allows easier removal of the oil from the work pieces after they have been formed. Differing dilutions allow change in consistency as suitable for the applications required as outlined below:

Dilution Ratio - Water : Oil

Neat

1 : 1

2 : 1

Paste Consistency

Thick white paste

Creamy paste

Watery paste

Features & Benefits:

- Extreme pressure additives incorporated into the product
 - Provides excellent lubricity thereby minimising dye pickup & metal tearing or scratching
- Excellent emulsification properties
 - Allows for easy removal of oil from work pieces after the forming operation
- Anti-corrosion additives incorporated
 - Provides excellent anti-corrosion of work pieces

Physical Properties:

Test	Units	Result
Density	gm/ml	0.96 typ.
Appearance		White creamy paste
Emulsion @ 10% in water		Stable
pH (Neat)		9.85
pH (10% in water)		9.60

Health & Safety:

Syntol Lubriform 788 is a petroleum based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Lubriform 788 is kept to a minimum. At no time should Syntol Lubriform 788 be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Lubriform 788 MSDS. For further H&S advice contact Syntol NZ Ltd. Phone (09) 634 6004.

Disclaimer:

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.