



Lubriform L44H

Product Description

Lubriform L44H is a light duty forming / punching oil which evaporates fully from the work-piece.

Product Applications

Applicable for light forming and punching operations of mild & medium tensile steels, aluminium, and copper alloys. Lubriform L44H is especially applicable where a fully evaporative forming oil is advantageous.

Features & Benefits

- Extreme pressure additives incorporated into the product
- Light viscosity
- Fully evaporative fluid
- Provides excellent lubricity thereby minimizing dye pickup & metal tearing or scratching
- Residues on work pieces are kept to a minimum.
- Dries after several days thereby minimizing downstream operations.

Physical Properties

Test	Units	Result
Density	gm/ml	0.83typ.
Appearance		Clear/bright colourless fluid.
Solids	% w/w	N/A
Flash Point	C	63

Health & Safety

Syntol Lubriform L44H is a petroleum based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Lubriform L44H is kept to a minimum. At no time should Syntol Lubriform L44H be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Lubriform L44H MSDS. For further H&S advice contact Syntol NZ Ltd. Phone 09 6346004.

Disclaimer

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.