



# Lubriform L75

## Product Description

A light duty forming / punching oil.

## Product Applications

Is applicable for light forming & punching operations of mild & medium tensile steels, aluminium, & copper alloys.

## Features & Benefits

- Extreme pressure additives incorporated into the product
  - Provides excellent lubricity thereby minimizing dye pickup & metal tearing or scratching
- Anti-corrosion additives incorporated
  - Provides excellent anti-corrosion of work pieces
- Light viscosity
  - Residues on work pieces are kept to a minimum

## Physical Properties

Test	Units	Result
Density	gm/ml	0.83typ.
Appearance		Clear/bright dark brown fluid.
Solids	% w/w	8

## Health & Safety

Syntol Lubriform L75 is a petroleum (kerosene) based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Lubriform L75 is kept to a minimum. At no time should Syntol Lubriform L75 be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol Lubriform L75 MSDS. For further H&S advice contact Syntol NZ Ltd. Phone 09 6346004.

## Disclaimer

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.