

Solvo SE 110



Product Description

Solvo SE110 spark erosion fluid designed for the modern spark erosion equipment as are in use today. It has very low aromatic content thereby minimizing risk to seals & rubber in the spark erosion machines as well as being Health & Safety responsible.

Product Applications

For use in all spark erosion machines. Has a light viscosity enabling fine finish work to be performed to expectation.

Features & Benefits

- Low aromatic content
- Low odour
- Low viscosity
- Not classed as a Class 3 flammable good
- Minimizes risk of seal swelling & is environmentally & Health & Safety responsible
- Operator acceptance
- Provides excellent surface finish
- Minimal restrictions on storage. Is however FLAMMABLE given appropriate conditions

Physical Properties

Test	Units	Result
Appearance		Clear/bright colorless liquid
Density	g/ml	0.81
Viscosity@25C	Cst	2.89
Flash point (Pensky Martens)	°C	113
Aromatic content	% m/m	1.0% max.
IBP	°C	243
FBP	°C	259

Health & Safety

Syntol Solvo SE 110 is a moderately toxic solvent. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Syntol Solvo SE 110 is kept to a minimum. At no time should Solvo SE 110 be disposed of into sewers. Disposal of Syntol Solvo SE 110 into storm water drains or other waterways should always be avoided. If spillage occurs contact your local council authority or refer to the Syntol Solvo SE 110 MSDS. For further advice refer to Syntol NZ Ltd. Phone 09 6346004.

Disclaimer

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.