

# Timber Finishing Oil (TFO)



## Product Description:

A lubricant specifically designed to lubricate machinery such as wood lathe beds.

## Product Applications:

Applicable for all lathes machining wood or wood like products. Apply directly either manually or via the automatic dispensing systems as on many machines, to the bed and slides of the lathe. The solvent base evaporates from the wood & lathe to leave a small amount of residue only.

## Features & Benefits:

- Lubricity agent incorporated into the product
  - Provides excellent lubricity thereby minimizing metal to metal wear.
- Anti-corrosion additives incorporated
  - Provides excellent anti-corrosion of lathe machinery.
- Light solvent base
  - Residues on wood & machinery are kept to a minimum.
- Fungicide package incorporated
  - Protects timber from fungal attack after machining.

## Physical Properties:

Test	Units	Result
Density	gm/ml	0.83typ.
Appearance		Clear/bright light amber fluid.
Solids	% w/w	23
Flash Point	C	38

## Health & Safety:

Syntol TFO is a petroleum (white spirit) based product. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Syntol TFO is kept to a minimum. At no time should Syntol TFO be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Syntol TFO MSDS. For further H&S advice contact Syntol NZ Ltd. Phone (09) 634 6004.

## Disclaimer:

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.