

Plastics Industry Product Range



Mineral Oil Lubricants:

Syntol Hydratek 32-46-68:

Hydraulic Oil series formulated from hydro-cracked virgin base stocks.
Available in ISO 32, 46 & 68 viscosity grades.

- Meets or exceeds: DIN51524, Part II: Cincinnati Machine P-68, P-69, P-70: US Steel 126,127: AFNOR NFE 48-603 (HM): Vickers M-2950-S, I-286-S3: Denison HF-2, HF-0.
- Superior anti-wear & anti-oxidation properties ensuring longer oil drain life.
- Excellent hydrolytic stability enabling superior filtration performance
- Excellent anti-foam & air release properties giving greater oxidation stability.

Pack size available: 20 litres, 205 litres

Syntol Slidelube 68 & 220:

Premium quality slide-way lubricants.

- Applicable for all horizontal & vertical slides requiring an ISO 68 or ISO 220 oil.
- Excellent tackiness for adherence to slides.
- Excellent anti-corrosion, friction modifier & extreme pressure additives incorporated for enhanced performance.

Pack size available: 20 litres, 205 litres

Soluble Metal Working Fluids:

Syntol ProCut S866:

Micro-emulsion soluble cutting fluid incorporating the latest technology to provide exceptional lubricity, cleanliness, corrosion protection, & bio-stability.

- True multi-metal machining fluid.
- Excellent corrosion protection of lathe, CNC or work-pieces.
- Inherently bio-stable enabling longer drain periods & no workplace smells.
- Low toxicity additives for enhanced worker acceptance.

Pack size available: 5 litres, 20 litres, 205 litres

Syntol Aquacut 660:

Full synthetic high performance soluble cutting fluid for use on all types of machining operations & metals.

- Inherent bio-stability thereby allowing intermittent use of lathes & CNC's without coolant going off.
- Excellent corrosion protection.
- Excellent tramp oil tolerance giving transparent coolant even with severe tramp oil contamination.

Pack size available: 20 litres, 205 litres

Rust Preventatives:

Syntol DM Spray:

Soft waxy film type rust preventative providing optimum dewatering & corrosion protection of dies & moulds.

- Heavy duty rust preventative for extended storage periods
- Easily removed with solvents such as white spirits or turpentine.
- Excellent dewatering properties.

Pack size available: 5 litres, 20 litres

Syntol Cortek RP85:

Light greasy film rust preventative which possesses excellent de-watering & corrosion protection characteristics.

- Provides 3 – 6 months protection of moulds when stored indoors.
- Excellent de-watering properties eliminating spot rusting
- Light carrier solvent for a quicker dry.
- Minimal creep of fluid to crevices or areas where rust preventative is not wanted.

Pack size available: Aerosol, 5 litres, 20 litres, 205 litres

Syntol Solvo SE110:

Premium quality spark erosion fluid.

- Elevated Flash Point (PMCC 110C) for enhanced Health & Safety protection.
- Non- aromatic containing fluid protects hoses & parts from solvent degradation.
- Low odour for worker acceptance.

Pack size available: 205 litres

www.syntol.com