

# Slidelube 68, 220



## Product Description:

Premium quality slideway lubricants for all horizontal & vertical slides as employed in metalworking, plastic injection & many other industrial machines.

## Product Applications:

Applicable for all horizontal or vertical slides where a tacky oil with anti-slip & friction modified properties are required.

## Features & Benefits:

- Tackiness additive & anti-corrosion package incorporated
- Anti-slip & friction modifying properties incorporated
- Minimizes oil loss on slides & protects machinery from corrosion.
- Provides excellent lubrication & avoids slip / stick seizures on slides.

## Physical Properties:

Test	Units	Slidelube 68	Slidelube 220
Density	gm/ml	0.89 typ.	0.91 typ.
Appearance		Clear/bright amber fluid	Clear/bright brown fluid
Viscosity @ 40C	Cst	66 – 70	218 - 222

## Health & Safety:

Syntol Slidelube 68 & Slidelube 220 are petroleum based products. It is recommended as with all industrial oils & cleaners that repeated or prolonged contact with Slidelube 68 & 220 is kept to a minimum. At no time should Slidelube 68 & 220 be disposed down sewers, storm water, or any other waterway. If spillage occurs contact your local council authority or refer to the Slidelube 68 or Slidelube 220 MSDS. For further H&S advice contact Syntol NZ Ltd. Phone (09) 634 6004.

## Disclaimer:

All reasonable care has been taken to ensure the information contained herein is accurate at the time of printing. However Syntol NZ Ltd accepts no tortuous or contractual liability for any loss or damages suffered as a consequence of the reliance on the information & advice contained herein.